



## AENOR Product Certificate



034/001374

AENOR certifies that the organization

### EPIFANIO CAMPO, S.L.

registered office CL CRUCEIRO, S/N 36990 VILLALONGA - SANXENXO (Pontevedra - España)

supplies **Clay roofing tiles and fittings**

in compliance with UNE-EN 1304:2014 (EN 1304:2013)

Nº Technical Form 1040201 (see annex)

Production site FIEITEIRA S/N ALBIXOI 15685 MESÍA (A Coruña - España)

Certification scheme This Certificate has been granted in accordance with the stipulations of AENOR Specific Rules RP 034.02

This certificate supersedes 034/001374, dated 2021-10-15



First issued on 2009-11-24  
Modified on 2023-02-20  
Validity 2028-02-20

Rafael GARCÍA MEIRO  
CEO



## AENOR MARK FOR CLAY ROOFING TILES AND FITTINGS

### TECHNICAL FORM N°: 1040201

Stamp and signature:	MANUFACTURER:	EPIFANIO CAMPO, S.L.					
	MADE IN:	MESÍA (A CORUÑA)					
	TILE DESCRIPTION:	OVER & UNDER TILE EN 1304					
	BRAND NAME:	TEJA CAMPO 40x15x12					
<b>PRODUCT TECHNICAL CHARACTERISTICS</b>							
<b>MANUFACTURER GUARANTEED VALUES</b>				<b>AENOR REQUIRED VALUES</b>			
<b>REQUIRED</b>							
<b>Nominal dimensions (mm)</b>				Structural characteristics (% faults)	ISO 2859-1	LCA 2,5 (I)	LCA 2,5 (I)
	Length	Width					
Individuals	X	400		Length tolerance (%)	EN 1024	± 2,0	± 2,0
Overlap							
<b>Over and Under Tiles</b>				Width tolerance (%) (not applicable in Over and Under tiles)	EN 1024	N/A	N/A
	Maximum width	Minimum width					
	150	114		Uniformity of the transverse profile (mm) (Only for Over and Under Tiles)	EN 1024	≤ 15	≤ 15
<b>Impermeability</b>							
Category 1	X	Test method 1		EN 1024	EN 1024	≤ 15	≤ 15
Category 2		Test method 2	X				
<b>Frost resistance</b>				Camber/Twist (%)	EN 1024	≤ 1,5	≤ 1,5
Level 1 (n° cycles without damages ≥ 150)			X				
Level 2 (n° cycles without damages ≥ 90)				Impermeability	EN 539-1	≤ 0,01	≤ 0,85
<b>OPTIONAL CHARACTERISTICS ANNEX D RP 34 02</b>							
		YES	NO	EN 539-1	EN 539-1	≤ 0,01	≤ 0,85
Impermeability (D.2 RP 34.02)			X				
Frost Resistance (D.3 RP 34.02)			X	D.2 RP 34.02	D.2 RP 34.02	N/A	N/A
<b>TILE SKETCH</b>							
				Flexural strength (N)	EN 538	≥ 4000	≥ 1000
				Frost resistance (cycles)	EN 539-2	≥ 150	≥ 150
					D.3 RP 34.02	N/A	N/A
				Fire reaction performance	EN 13501-1	A1	A1
				External fire performance	EN 13501-5	Broof (t1/t2/t3)	Broof (t1/t2/t3)
<b>Note: The values guaranteed by the manufacturer for the different characteristics are applicable from 2022-10-26</b>							
<b>Additional information given by the manufacturer <sup>(1)</sup></b>							
Unitary mass (in grams):							
Roof tiles number in m <sup>2</sup> (with one decimal):						VARIABLE ACCORDING TO OVERLAP	
Length distance between battens (cm):							
Surface finish:							
Mass coloration: RED, BROWN, ANTHRACITE							
Fixing types: STAINLESS STEEL HOOKS, SCREWS, POLYURETHANE FOAM AND PROFILES							
Further information:							
<b>Accessories:</b>							
UNDER RIDGE PIECE, EAVE ROOF TILE, HIP-RIDGE AND STRAIGHT RAKE							

<sup>(1)</sup> This information is out of the AENOR Mark and ENAC accreditation scopes. AENOR is not responsible for the information in this square

Water repellent treatment if is requested