

AENOR



AENOR Product Certificate



034/001374

AENOR certifies that the organization

EPIFANIO CAMPO, S.L.

registered office CL CRUCEIRO, S/N 36990 VILLALONGA - SANXENXO (Pontevedra - España)

supplies **Clay roofing tiles and fittings**

in compliance with UNE-EN 1304:2020 (EN 1304:2013)

Nº Technical Form 1040201 (see annex)

Production site FIEITEIRA S/N ALBIXOI 15685 MESÍA (A Coruña - España)

Certification scheme This Certificate has been granted in accordance with the stipulations of AENOR Specific Rules RP 034.02

This certificate supersedes 034/001374, dated 2023-02-20

First issued on 2009-11-24

Modified on 2026-06-10

Validity 2031-06-10

Rafael GARCÍA MEIRO
CEO



AENOR CONFÍA S.A.U.
Génova, 6. 28004 Madrid. España
Tel. 91 432 60 00.- www.aenor.com

AENOR MARK FOR CLAY ROOFING TILES AND FITTINGS

TECHNICAL FORM Nº: 1040201



MANUFACTURER:	EPIFANIO CAMPO, S.L.
MADE IN:	MESÍA (A CORUÑA)
TILE DESCRIPTION:	OVER & UNDER TILE EN 1304
BRAND NAME:	TEJA CAMPO 40x15x12

PRODUCT TECHNICAL CHARACTERISTICS

MANUFACTURER GUARANTEED VALUES				AENOR REQUIRED VALUES			
REQUIRED				Structural characteristics (% faults)	ISO 2859-1	LCA 2,5 (I)	LCA 2,5 (I)
Nominal dimensions (mm)							
		Length	Width	Length tolerance (%)	EN 1024	± 2,0	± 2,0
Individuals	X	400					
Overlap							
Over and Under Tiles				Width tolerance (%) (not applicable in Over and Under tiles)	N/A	N/A	N/A
	Maximum width	Minimum width					
	150	114					
Impermeability				Uniformity of the transverse profile (mm) (Only for Over and Under Tiles)	EN 1024	≤ 15	≤ 15
Category 1	X	Test method 1					
Category 2		Test method 2	X				
Frost resistance				Camber/Twist (%)	EN 1024	≤ 1,5	≤ 1,5
Level 1 (nº cycles without damages ≥ 150)			X				
Level 2 (nº cycles without damages ≥ 90)							
OPTIONAL CHARACTERISTICS ANNEX D RP 34.02				Impermeability	EN 539-1	≤ 0,01	≤ 0,8
	YES	NO					
Impermeability (D.2 RP 34.02)		X					
Frost Resistance (D.3 RP 34.02)		X					
TILE SKETCH				Flexural strenght (N)	EN 538	≥ 2000	≥ 1000
<p style="text-align: center;">Piece without water repellent treatment</p>							
				Fire reaction performance	EN 13501-1	A1	A1
				Note: The values guaranteed by the manufacturer for the different characteristics are applicable from 2025-10-14			
Additional information given by the manufacturer ⁽¹⁾							
Unitary mass (in grams):				1330			
Roof tiles number in m ² (with one decimal):				31,9 (WITH OVERLAP OF 7 cm)			
Length distance between battens (cm):				VARIABLE ACCORDING TO OVERLAP			
Surface finish:							
Mass coloration:				RED, ANTHRACITE			
Fixing types:				STAINLESS STEEL HOOKS, SCREWS AND POLYURETHANE FOAM			
Further information:							
Accessories:							
EAVE ROOF TILE, PERFORATED ROOF TILE, HIP-RIDGE, UNDER RIDGE TILE, STRAIGHT RAKE TILE, RIDGE END CAP							

Stamp and signature:

Construction details where the material named in this technical form have been placed:

(For the final qualification, this technical form shall be stamped and signed by the manufacturer)

⁽¹⁾ This information is out of the AENOR Mark and ENAC accreditation scopes. AENOR is not responsible for the information in this square